

Z MASTER®

3000 SERIES

PROGRESS ALWAYS CUTS A STRAIGHT LINE.



The Z Master® 3000 Series proves you can have it all with performance, durability and value.

3.7–6.5
Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.

MyRIDE® SUSPENSION SYSTEM



MyRIDE® Suspension System¹ features a rear shock adjustable operator platform that isolates bumps and vibrations.

¹Models 72932 and 72936 only. See pages 6-7 for details.



COMMERCIAL ENGINES

Kawasaki® FX and Kohler® engines provide professional quality performance. Heavy-duty canister air filtration system protects engine.



TURBO FORCE® TOUGH

The deep, adjustable TURBO FORCE deck works with the high-torque diesel engine for outstanding results at higher ground speeds.



INFO AT A GLANCE

The easy-to-see instrument panel includes a digital hour meter, fuel gauge, voltage meter and diagnostics for quick troubleshooting.

| | 72952 | | 72949 | | 72932 MyRIDE® Suspension System | | 72950 | | 72958 | | 72936 MyRIDE Suspension System | | 72959 | |
|--------------------------------------|---|----------|---|----------|---|----------|---|----------|---|----------|---|----------|---|----------|
| POWER SYSTEM | | | | | | | | | | | | | | |
| Commercial Engines at 3600 RPM* | 20.5 hp Kawasaki® FX (726cc) | | 24.5 hp Kawasaki FX (852cc) | | 24.5 hp Kawasaki FX (852cc) | | 25.5 hp Kawasaki FX (852cc) | | 25 hp Kohler Command PRO EFI (747cc) | | 25.5 hp Kawasaki FX (852cc) | | 25 hp Kohler® Command PRO (747cc) | |
| Starter | Electric | | Electric | | Electric | | Electric | | Electric | | Electric | | Electric | |
| Heavy-Duty Canister Air Cleaner | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Drive Tires | 23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm) | | 23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm) | | 23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm) | | 24" x 12" – 12" (61 x 30.5 – 30.5 cm) | | 24" x 12" – 12" (61 x 30.5 – 30.5 cm) | | 24" x 12" – 12" (61 x 30.5 – 30.5 cm) | | 24" x 12" – 12" (61 x 30.5 – 30.5 cm) | |
| Caster Tires | 13" x 5" – 6" (33 x 12.7 – 15.2 cm) Pneumatic | | 13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic | | 13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic | | 13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic | | 13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic | | 13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic | | 13" x 6.5" – 6" (33 x 16.5 – 15.2 cm) Pneumatic | |
| Fuel/Capacity | Gas/8-Gal (30.3 L) | | Gas/8-Gal (30.3 L) | | Gas/8-Gal (30.3 L) | | Gas/8-Gal (30.3 L) | | Gas/8-Gal (30.3 L) | | Gas/8-Gal (30.3 L) | | Gas/8-Gal (30.3 L) | |
| Digital Hour Meter | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Hydraulic Drive System | Unitized Pumps & Wheel Motors | | Unitized Pumps & Wheel Motors | | Unitized Pumps & Wheel Motors | | Unitized Pumps & Wheel Motors | | Unitized Pumps & Wheel Motors | | Unitized Pumps & Wheel Motors | | Unitized Pumps & Wheel Motors | |
| Pump | 12cc/rev | | 12cc/rev | | 12cc/rev | | 12cc/rev | | 12cc/rev | | 12cc/rev | | 12cc/rev | |
| Wheel Motor | 14.6 cir | | 14.6 cir | | 14.6 cir | | 14.6 cir | | 14.6 cir | | 14.6 cir | | 14.6 cir | |
| Maximum Forward Speed | 8.5 mph (13.7 km/h) | | 8.5 mph (13.7 km/h) | | 8.5 mph (13.7 km/h) | | 10 mph (16.1 km/h) | | 10 mph (16.1 km/h) | | 10 mph (16.1 km/h) | | 10 mph (16.1 km/h) | |
| Clutch | Electromagnetic | | Electromagnetic | | Electromagnetic | | Electromagnetic | | Electromagnetic | | Electromagnetic | | Electromagnetic | |
| MOWING DECKS | | | | | | | | | | | | | | |
| Deck Size | 48" (121.9 cm) | | 52" (132.1 cm) | | 52" (132.1 cm) | | 60" (152.4 cm) | | 60" (152.4 cm) | | 60" (152.4 cm) | | 72" (182.9 cm) | |
| Cutting Deck | 7-Gauge TURBO FORCE® | | 7-Gauge TURBO FORCE | | 7-Gauge TURBO FORCE | | 7-Gauge TURBO FORCE | | 7-Gauge TURBO FORCE | | 7-Gauge TURBO FORCE | | 7-Gauge TURBO FORCE | |
| Bullnose Bumper | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Adjustable Discharge Baffle | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Rubber Discharge Chute | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Deck Lift Design | Extension Spring | | Extension Spring | | Extension Spring | | Extension Spring | | Extension Spring | | Extension Spring | | Extension Spring | |
| Spindle Housings | 9" (22.9 cm) Dia. Cast Aluminum | | 9" (22.9 cm) Dia. Cast Aluminum | | 9" (22.9 cm) Dia. Cast Aluminum | | 9" (22.9 cm) Dia. Cast Aluminum | | 9" (22.9 cm) Dia. Cast Aluminum | | 9" (22.9 cm) Dia. Cast Aluminum | | 9" (22.9 cm) Dia. Cast Aluminum | |
| 1" (2.5 cm) Heavy-Duty Spindle Shaft | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Spindle Bearings | Maintenance-Free | | Maintenance-Free | | Maintenance-Free | | Maintenance-Free | | Maintenance-Free | | Maintenance-Free | | Maintenance-Free | |
| Cutting Height | 1.0" – 5.5" (2.5 – 14 cm) | | 1.0" – 5.5" (2.5 – 14 cm) | | 1.0" – 5.5" (2.5 – 14 cm) | | 1.0" – 5.5" (2.5 – 14 cm) | | 1.0" – 5.5" (2.5 – 14 cm) | | 1.0" – 5.5" (2.5 – 14 cm) | | 1.0" – 5.5" (2.5 – 14 cm) | |
| Deck Depth | 5.5" (14 cm) | | 5.5" (14 cm) | | 5.5" (14 cm) | | 5.5" (14 cm) | | 5.5" (14 cm) | | 5.5" (14 cm) | | 5.5" (14 cm) | |
| Blades | .204" (.5 cm) Heat-Treated Steel | | .204" (.5 cm) Heat-Treated Steel | | .204" (.5 cm) Heat-Treated Steel | | .204" (.5 cm) Heat-Treated Steel | | .204" (.5 cm) Heat-Treated Steel | | .204" (.5 cm) Heat-Treated Steel | | .204" (.5 cm) Heat-Treated Steel | |
| Blade Tip Speed | 18,500+ ft/min | | 18,500+ ft/min | | 18,500+ ft/min | | 18,500+ ft/min | | 18,500+ ft/min | | 18,500+ ft/min | | 18,500+ ft/min | |
| Belt Construction | Aramid Fiber V-Belt | | Aramid Fiber V-Belt | | Aramid Fiber V-Belt | | Aramid Fiber V-Belt | | Aramid Fiber V-Belt | | Aramid Fiber V-Belt | | Aramid Fiber V-Belt | |
| Anti-Scalp Rollers | 3 Standard, 1 Optional | | 3 Standard, 1 Optional | | 4 Standard, 1 Optional | | 4 Standard, 1 Optional | | 4 Standard, 1 Optional | | 4 Standard, 1 Optional | | 4 Standard, 1 Optional | |
| Carrier Frame Construction | 3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge) | | 3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge) | | 3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge) | | 3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge) | | 3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge) | | 3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge) | | 3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge) | |
| FEATURES | | | | | | | | | | | | | | |
| Steering Controls | 1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened | | 1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened | | 1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened | | 1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened | | 1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened | | 1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened | | 1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened | |
| Operator Seat | Deluxe Suspension with 3-D Isolation Mounts | | Deluxe Suspension with 3-D Isolation Mounts | | MyRIDE Suspension System | | Deluxe Suspension with 3-D Isolation Mounts | | Deluxe Suspension with 3-D Isolation Mounts | | MyRIDE Suspension System | | Deluxe Suspension with 3-D Isolation Mounts | |
| Arm Rests | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Seat Suspension System | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Folding ROPS | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Storage Compartment | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Foot Pedal Deck Lift | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | | Standard | |
| Z Stand | Optional | | Optional | | Optional | | Optional | | Optional | | Optional | | Optional | |
| Floor Pan | Pierced, Extruded Tread; No-Tools Deck Access | | Pierced, Extruded Tread; No-Tools Deck Access | | Pierced, Extruded Tread; No-Tools Deck Access | | Pierced, Extruded Tread; No-Tools Deck Access | | Pierced, Extruded Tread; No-Tools Deck Access | | Pierced, Extruded Tread; No-Tools Deck Access | | Pierced, Extruded Tread; No-Tools Deck Access | |
| WEIGHTS AND MEASUREMENTS | | | | | | | | | | | | | | |
| Weight | 1,048 lbs. | 475.4 kg | 1,085 lbs. | 492.1 kg | 1,185 lbs. | 537.5 kg | 1,165 lbs. | 528.4 kg | 1,185 lbs. | 537.5 kg | 1,185 lbs. | 537.5 kg | 1,255 lbs. | 569.3 kg |
| ROPS Height (Folded) | 46.8" | 118.9 cm | 46.8" | 118.9 cm | 46.8" | 118.9 cm | 46.8" | 118.9 cm | 46.8" | 118.9 cm | 46.8" | 118.9 cm | 46.8" | 118.9 cm |
| ROPS Height (Upright) | 70.5" | 179.1 cm | 70.5" | 179.1 cm | 70.5" | 179.1 cm | 70.5" | 179.1 cm | 70.5" | 179.1 cm | 70.5" | 179.1 cm | 70.5" | 179.1 cm |
| Deck Clearance Width | 49.7" | 126.2 cm | 53.7" | 136.4 cm | 61.7" | 156.7 cm | 61.7" | 156.7 cm | 61.7" | 156.7 cm | 61.7" | 156.7 cm | 61.7" | 156.7 cm |
| Deflector Width | 63.6" | 161.5 cm | 67.6" | 171.7 cm | 75.7" | 192.3 cm | 75.7" | 192.3 cm | 75.7" | 192.3 cm | 75.7" | 192.3 cm | 75.7" | 192.3 cm |
| Length | 79.2" | 201.2 cm | 79.2" | 201.2 cm | 83.1" | 211.1 cm | 83.1" | 211.1 cm | 83.1" | 211.1 cm | 83.1" | 211.1 cm | 83.1" | 211.1 cm |

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.