

2.6–5.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



TRACTION AND HANDLING

A wide stance and optimal balance enhance hillside stability and control. Operators can shift weight as needed to further enhance performance.



CUSHIONED SUSPENSION

Flex-Ride operator platform suspension self-compensates for operators of all sizes, resulting in less fatigue and higher productivity throughout the day.



2-IN-1 VERSATILITY

Foldable operator platform instantly converts the machine to a walk-behind. It easily lowers the bagger and vertically back down when it's time to ride, saving time and trailer space.



POWERED BAGGER

Compact side-mounted soft twin bagger and vertically mounted blower allow maneuverability in tight spaces and maximum visibility.

	74534 79534 CARB Model	74536	74504 79504 CARB Model	79518	74505 79505 CARB Model	74519	74513							
POWER SYSTEM														
Commercial Engines at 3600 RPM*	15 hp Kawasaki [†] FS (541cc)	15 hp Kawasaki FS (541cc)	22 hp Kawasaki FX (726cc)	23 hp Kohler [†] Command PRO [®] EFI (747cc)	22 hp Kawasaki FX (726cc)	25 hp Kohler Command PRO EFI (747cc)	25 hp Kohler Command PRO EFI (747cc)							
Starter	Electric	Electric	Electric	Electric	Electric	Electric	Electric							
Heavy-Duty Canister Air Cleaner	N/A	Standard	Standard	Standard	Standard	Standard	Standard							
Drive Tires	18" x 8.5" – 8" (45.7 x 21.6 – 20.3 cm)	18" x 9.5" – 8" (45.7 x 24.1 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)							
Caster Tires	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic	11" x 4" – 5" (27.9 x 10.2 – 12.7 cm) Flat-Free Semi-Pneumatic							
Fuel/Capacity	Gas/7.8 Gal (29.5 L)	Gas/7.8 Gal (29.5 L)	Gas/10.5 Gal (39.7 L)	Gas/10.5 Gal (39.7 L)	Gas/10.5 Gal (39.7 L)	Gas/10.5 Gal (39.7 L)	Gas/10.5 Gal (39.7 L)							
Digital Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard	Standard							
Hydraulic Drive System	Pumps & Wheel Motors	Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors							
Pump	10cc/rev	10cc/rev	10cc/rev	10cc/rev	10cc/rev	10cc/rev	10cc/rev							
Wheel Motor	10 cir	10 cir	10 cir	10 cir	10 cir	10 cir	10 cir							
Maximum Forward Speed	8 mph (12.9 km/h)	8 mph (12.9 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)							
Clutch	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic							
MOWING DECKS														
Deck Size	36" (91.4 cm)	40" (101.6 cm)	48" (121.9 cm)	48" (121.9 cm)	52" (132.1 cm)	52" (132.1 cm)	60" (152.4 cm)							
Cutting Deck	7-Gauge TURBO FORCE [™]	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE							
Bull-Nose Bumper	Standard	Standard	Standard	Standard	Standard	Standard	Standard							
Adjustable Discharge Baffle	Standard	Standard	Standard	Standard	Standard	Standard	Standard							
Rubber Discharge Chute	Standard	Standard	Standard	Standard	Standard	Standard	Standard							
Deck Lift Design	Compression Spring	Compression Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring							
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Iron	9 3/8" (23.8 cm) Diameter Cast Iron	9 3/8" (23.8 cm) Diameter Cast Iron	9 3/8" (23.8 cm) Diameter Cast Iron	9 3/8" (23.8 cm) Diameter Cast Iron	9 3/8" (23.8 cm) Diameter Cast Iron	9 3/8" (23.8 cm) Diameter Cast Iron							
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard	Standard	Standard	Standard	Standard	Standard							
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free							
Cutting Height	1.0" – 5.0" (2.5 – 12.7 cm) .25" (.6 cm)	1.0" – 5.0" (2.5 – 12.7 cm) .25" (.6 cm)	1.5" – 5.0" (3.8 – 12.7 cm) .25" (.6 cm)	1.5" – 5.0" (3.8 – 12.7 cm) .25" (.6 cm)	1.5" – 5.0" (3.8 – 12.7 cm) .25" (.6 cm)	1.5" – 5.0" (3.8 – 12.7 cm) .25" (.6 cm)	1.5" – 5.0" (3.8 – 12.7 cm) .25" (.6 cm)							
Blades	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel	Heat-Treated Steel							
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min							
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt							
Anti-Scalp Rollers	N/A	N/A	Optional	Optional	Optional	Optional	Standard							
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)							
FEATURES														
Steering Controls	Twin Lever	Twin Lever	Twin Lever	Twin Lever	Twin Lever	Twin Lever	Twin Lever							
Operator Platform	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension	Foldable Operator Platform with Suspension							
WEIGHTS AND MEASUREMENTS														
Weight	833 lbs.	377.8 kg	844 lbs.	382.8 kg	890 lbs.	403.7 kg	881 lbs.	399.6 kg	898 lbs.	407.3 kg	895 lbs.	406 kg	941 lbs.	426.8 kg
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm
Deck Clearance Width	37.6"	95.5 cm	41.8"	106.2 cm	49.5"	125.7 cm	49.5"	125.7 cm	53.5"	135.9 cm	53.5"	135.9 cm	61.5"	156.2 cm
Deflector Width	51.6"	131.1 cm	55.8"	141.7 cm	63.5"	161.3 cm	63.5"	161.3 cm	67.5"	171.5 cm	67.5"	171.5 cm	75.5"	191.8 cm
Length (Platform Up)	61"	154.9 cm	57"	144.8 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	65"	165.1 cm
Length (Platform Down)	74"	188 cm	70"	177.8 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	79"	200.7 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.